



Model		TN-5080VM	TN-5080VM3 *	TUK-5080VM	TUK-5080VM3 *
Electric Motor	H.P.	5		5	
	R.P.M / Frame	1740 / 184	1750 / 184	1740 / 184	1750 / 184
	Volt./ Phase/ Amp.	208-230 / Single / 16.6-15	208-230 or 460 / Three / 23-21	208-230 / Single / 23.5-21.5	208-230 or 460 / Three / 14-13.2 or 6.6
Pump R.P.M		950		950	
Max. Working PSI.		175		175	
FAD- CFM	@ 90 PSI	18		18.3	
	@ 175 PSI	16.5		17	
TANK	Gal.	80		80	
	Style	Vertical		Vertical	
	Code	ASME / CRN		ASME / CRN	
Weight (Lbs)		550	535	560	560
Magnetic Starter		Yes		Yes	
Outlet Ball Valve		1/2"		1/2"	
Ext. Manual Drain		1/4"		1/4"	
Premium Package		Option		Option	



Model		TUK-50120VM	TUK-50120VM3 *	TUK-50120M	TUK-50120M3 *
Electric Motor	H.P.	5		5	
	R.P.M / Frame	1740 / 184	1750 / 184	1740 / 184	1750 / 184
	Volt./ Phase/ Amp.	208-230 / Single / 23.5-21.5	208-230 or 460 / Three / 14-13.2 or 6.6	208-230 / Single / 23.5-21.5	208-230 or 460 / Three / 14-13.2 or 6.6
Pump R.P.M		950		950	
Max. Working PSI.		175		175	
FAD- CFM	@ 90 PSI	18.3		18.3	
	@ 175 PSI	17		17	
TANK	Gal.	120		120	
	Style	Vertical		Horizontal	
	Code	ASME / CRN		ASME / CRN	
Weight (Lbs)		815	810	755	750
Magnetic Starter		Yes		Yes	
Outlet Ball Valve		1"		1"	
Ext. Manual Drain		1/4"		1/4"	
Premium Package		Option		Option	

* Three phase motor, customers must specify voltage (208-230 or 460 V) when ordering.

PUMA INDUSTRIES, INC.

1992 Airways Blvd. Memphis, TN 38114
 TEL:1-901-744-7979 FAX:1-901-744-7579

e-mail:sales@pumaaircenter.com
 http://www.pumaairusa.com

