








## Premium Package

● 059-404010		<b>VIBRATION DAMPER</b> w/ 3/8" HOLE Dimension: 4" x 4" x 1"
● 3353103		<b>LOW OIL SWITCH w/o Adapter</b>
● 2405302		<b>ELECTRIC AUTO WATER DRAIN VALVE w/ TIMER</b> Max PSI: 230 Adjustable Drain Cycle: 0.5-45 min Adjustable Purge time: 0.5-10 sec Drain Rate @ 100 PSI: 8.8 Pilot Pressure: 5-230 PSI Voltage: 115
● 022-ADV-001		<b>AIR ACTUATE AUTO WATER DRAIN VALVE</b> Max PSI: 300 Bowl Size: 4 oz.
● 2813056		<b>AFTERCOOLER (B.G MOUNT)</b> w/ 1" NPT PIPE THREAD HOLES*2
● 016-AWS050-001		<b>AIR WATER SEPERATOR 50CFM</b> Standard: Float Drain Automatic Water Drain: Optional Water Separation: Up to 1QT / per min

## Magnetic Motor Starter

● MS-50-1S		Rating: 5hp, 208-230volt, single phase Steel housing Built-in overload adjustable control from 22-34 amps, Manual reset button that can be switched to auto reset UL, CSA, CE certified
● MS-75-1S		Rating: 7.5hp, 208-230volt, single phase Steel housing Built-in overload adjustable control from 32-48 amps, Manual reset button that can be switched to auto reset UL, CSA, CE certified
● MS-100-1S		Rating: 10hp, 208-230volt, single phase Steel housing Built-in overload adjustable control from 43-65 amps, Manual reset button that can be switched to auto reset UL, CSA, CE certified
● MS-50-3S		Rating: 5hp, 208-230volt, three phase Steel housing Built-in overload adjustable control from 12-18 amps, Manual reset button that can be switched to auto reset UL, CSA, CE certified
● MS-75-3S		Rating: 7.5hp, 208-230volt, three phase Steel housing Built-in overload adjustable control from 17-24 amps, Manual reset button that can be switched to auto reset UL, CSA, CE certified
● MS-100-3S		Rating: 10hp, 208-230volt, three phase Steel housing Built-in overload adjustable control from 28-38 amps, Manual reset button that can be switched to auto reset UL, CSA, CE certified
● MS-150-3S		Rating: 15hp, 208-230volt, three phase Steel housing Built-in overload adjustable control from 43-65 amps, Manual reset button that can be switched to auto reset UL, CSA, CE certified

## Hand Carry Tank / Air Keg

● AST-05A		<b>ALUMINUM HAND CARRY TANK</b> Max. Working pressure: 125 PSI The unit is shipped with: 1pc 0-160 psi pressure gauge 1pc Brass manifold with shutoff and safety valves 1pc Drain Valve Weight: 13 Lbs	● 2416101		<b>CARRY TANK MANIFOLD</b> Size: 1/2" Relief Pressure: 150 PSI
● AST-08U		<b>ASME STEEL AIR KEG</b> Max. Working pressure: 175 PSI The unit is shipped with : 4pcs 1/4" female quick couplers with 3/8" NPT 1pc ASME safety valve 1pc 0-200 psi pressure gauge 1pc Automatic shut-off inlet valve w/1/4" male quick coupler 1pc Drain valve 1pc Plug (located on expansion port) Weight: 30 Lbs	● 2416104		<b>CARRY TANK MANIFOLD</b> Size: 1/2" Relief Pressure: 125 PSI *Work along with AST-05A 5 Gal Aluminum tank
			● 2414048		<b>AUTOMATIC SHUT-OFF INLET VALVE</b> 90 ° ELBOW 3/8" NPT Male / Male Thread

Legend : ● Blue Retail Package ● Yellow Retail Package ● White Box Only

