

- Oil-less design allows units to be mounted in any orientation.
- Deep cooling fin design on cylinder head and cylinders for high efficiency cooling.
- Oversized motor cooling fan prevent motor from overheating.
- Continuous duty cycle for DE and PD series, 60% duty cycle for DC series.
- Ideal for off-road vehicles, RV, agriculture, construction, motorsports, and applications where on-board air is needed.



Model	DC02	DC05K	DE05	DE07
H.P.	1/4	1/2	1/2	3/4
R.P.M.	3000	2700	2100	3000
Amp.(A) / Battery (AH)	@ 12VDC	18 / 20	28 / 30	32 / 30
	@ 24VDC	8 / 10	19 / 20	16 / 20
Max. PSI	135	135	135	135
FAD-CFM	Disp.	1.2	1.9	2.3
	40 PSI	0.72	1.2	1.52
	90 PSI	0.48	0.8	0.96
Duty Cycle	60%	60%	Continuous	Continuous
Noise (dB)	68	70	72	78
Dimension (in.)	9 x 4.7 x 7	11.8 x 4.3 x 6.7	12.2 x 7.5 x 11	12.2 x 7.5 x 11
Wts. Lbs.	6	6	18	19
Accessories		Overload breaker, Solenoid Relay		



Model	DE08K	PD1006	PD1012A
H.P.	1	3/4	3/4
R.P.M.	3400	3000	3000
Amp.(A) / Battery (AH)	@ 12VDC	80 / 100	46 / 50
	@ 24VDC	40 / 50	22 / 30
Max. PSI	135	135	135
FAD-CFM	Disp.	4.6	3.3
	40 PSI	2.7	2.0
	90 PSI	2.0	1.36
Tank Cap. (GAL.)	-	1.5	3.0
Duty Cycle	Continuous	Continuous	Continuous
Noise (dB)	80	78	78
Dimension (in.)	14.2 x 6.7 x 8.66	19.3 x 8.3 x 17.3	21.5 x 7.5 x 19
Wts. Lbs.	10.5	31	30
Accessories	Overload breaker, Solenoid Relay	Pressure switch, Overload breaker, 6.5 ft jump cable	Aluminum tank, Pressure switch, Overload breaker, 6.5 ft jump cable

