

- Compact and portable designs.
 - Patented pump design for lower noise and improved cooling (features on PN and LA models.)
 - Maintenance-free.
 - All models are driven by induction motors
 - with overload protection.
- Ideal for home and professional applications.



Model	PN1004PK	LA5706	LA5721	LA9003A
H.P.	0.5	1	1	1.5
R.P.M.	3450	3450	3450	3450
C.F.M.	@ 40 PSI	1.1	3	4.8
	@ 90 PSI	0.7	2.2	3.6
Max. PSI	135	135	135	135
Volt. /Phase	115 / Single	115 / Single	115 / Single	115 / Single
F.L. Amperage	3.0	6.5	6.5	13.5
Tank Cap. (GAL.)	1	1.5	2	3
Weight (Lbs)	23	33	38	31
Noise (dB)	68	76	78	82
Certificate	CSA	CSA	CSA	CSA
Accessories	25ft 1/4" coil hose, tire chuck, needle inflator			Aluminum tank



Model	WE1504C	WE1504CK	WE1508VP
H.P.	1.5	1.5	1.5
R.P.M.	1720	1720	1720
C.F.M.	@ 40 PSI	5.4	5.4
	@ 90 PSI	4.0	4.0
Max. PSI	125	125	125
Volt. /Phase	115 / Single	115 / Single	115 / Single
F.L. Amperage	12	12	12
Tank Cap. (GAL.)	4	4	8
Weight (Lbs)	88	105	88
Noise (dB)	70	70	70
Certificate	CSA	CSA	CSA
Accessories		100 ft 3/8" PU hose reel (removable)	

PUMA INDUSTRIES, INC.

1992 Airways Blvd. Memphis, TN 38114
 TEL:1-901-744-7979 FAX:1-901-744-7579

e-mail:sales@pumaaircenter.com
 http://www.pumaairusa.com

